



## N-channel Power MOSFET


PRODUCT SUMMARY	
$V_{DS}$ (V) at $T_J$ max.	650
$R_{DS(on)}$ max. at 25°C (mΩ)	$V_{GS}=10V$   360
$Q_g$ max. (nC)	30
$Q_{gs}$ (nC)	5.7
$Q_{gd}$ (nC)	8
Configuration	single

## Features

- New Technology For High Voltage Device
- $I_D=10A(V_{GS}=10V)$
- Ultra Low Gate Charge
- Improved  $dv/dt$  Capability
- RoHS Compliant



TO-220F



Schematic diagram

## Applications

- Switching Mode Power Supplies (SMPS)
- Power factor correction ( PFC )
- Uninterruptible Power Supply ( UPS )

ORDERING INFORMATION	
Device	SPC60R360G
Device Package	TO-220F
Marking	60R360G

ABSOLUTE MAXIMUM RATINGS ( $T_C = 25^\circ\text{C}$ , unless otherwise noted)			
Parameter	Symbol	Limit	Unit
Drain to Source Voltage	$V_{DSS}$	600	V
Continuous Drain Current (@ $T_C=25^\circ\text{C}$ )	$I_D$	10 <sup>(1)</sup>	A
Continuous Drain Current (@ $T_C=100^\circ\text{C}$ )		6.4 <sup>(1)</sup>	A
Drain current pulsed <sup>(2)</sup>	$I_{DM}$	30 <sup>(1)</sup>	A
Gate to Source Voltage	$V_{GS}$	$\pm 30$	V
Single pulsed Avalanche Energy <sup>(3)</sup>	$E_{AS}$	280	mJ
MOSFET $dv/dt$ ruggedness (@ $V_{DS}=0\sim 400V$ )	$dv/dt$	25	V/ns
Peak diode Recovery $dv/dt$ <sup>(4)</sup>	$dv/dt$	15	V/ns
Total power dissipation (@ $T_C=25^\circ\text{C}$ )	$P_D$	32.7	W
Derating Factor above 25°C		0.26	W/°C
Operating Junction Temperature & Storage Temperature	$T_{STG}, T_J$	-55 to + 150	°C
Maximum lead temperature for soldering purpose	$T_L$	260	°C
Mounting torque <sup>(5)</sup>		0.4~0.6	N.m

## Notes

1. Drain current is limited by maximum junction temperature.
2. Repetitive rating : pulse width limited by junction temperature.
3.  $L = 140\text{mH}$ ,  $I_{AS} = 2A$ ,  $V_{DD} = 50V$ ,  $R_G = 25\Omega$ , Starting at  $T_J = 25^\circ\text{C}$
4.  $I_{SD} \leq I_D$ ,  $di/dt = 100A/\mu\text{s}$ ,  $V_{DD} \leq 480V$ , Starting at  $T_J = 25^\circ\text{C}$
5. Mounting consideration for TO220 Fullpack:  
M3 screw plus flat washer is suggested, free of burr between devices and contact area,  
the devices are to be mounted to a hole not larger than 3.6mm in contact diameter (chamfer included).



**THERMAL CHARACTERISTICS**

Parameter	Symbol	Value	Unit
Thermal resistance, Junction to case	$R_{thjc}$	3.82	°C/W
Thermal resistance, Junction to ambient	$R_{thja}$	80	°C/W

**ELECTRICAL CHARACTERISTICS (  $T_C = 25^\circ\text{C}$  unless otherwise specified )**

Parameter	Symbol	Test conditions	Min.	Typ.	Max.	Unit
<b>Off Characteristics</b>						
Drain to source breakdown voltage	$BV_{DSS}$	$V_{GS}=0V, I_D=250\mu A$	600	--	--	V
Breakdown voltage temperature coefficient	$\Delta BV_{DSS} / \Delta T_J$	$I_D=250\mu A$ , referenced to $25^\circ\text{C}$	--	0.7	--	V/°C
Drain to source leakage current	$I_{DSS}$	$V_{DS}=600V, V_{GS}=0V$	--	--	1	$\mu A$
		$V_{DS}=600V, T_C=125^\circ\text{C}$	--	--	10	$\mu A$
Gate to source leakage current, forward	$I_{GSS}$	$V_{GS}=30V, V_{DS}=0V$	--	--	100	nA
Gate to source leakage current, reverse		$V_{GS}=-30V, V_{DS}=0V$	--	--	-100	nA
<b>On Characteristics</b>						
Gate threshold voltage	$V_{GS(TH)}$	$V_{DS}=V_{GS}, I_D=250\mu A$	2.5	3	3.5	V
Drain to source on state resistance	$R_{DS(ON)}$	$V_{GS}=10V, I_D=5A$	--	300	360	$m\Omega$
Forward Transconductance	$G_{fs}$	$V_{DS}=20V, I_D=5A$	--	8	--	S
<b>Dynamic Characteristics</b>						
Input capacitance	$C_{iss}$	$V_{GS}=0V, V_{DS}=50V, f=1\text{MHz}$	--	1030	--	pF
Output capacitance	$C_{oss}$		--	87	--	
Reverse transfer capacitance	$C_{rss}$		--	4.5	--	
Turn on delay time	$t_{d(on)}$	$V_{DS}=350V, I_D=10A, R_G=18\Omega, V_{GS}=10V$	--	9	--	ns
Rising time	$t_r$		--	4	--	
Turn off delay time	$t_{d(off)}$		--	50	--	
Fall time	$t_f$		--	5	--	
Total gate charge	$Q_g$	$V_{DS}=420V, V_{GS}=10V, I_D=10A$	--	23	30	nC
Gate-source charge	$Q_{gs}$		--	5.7	--	
Gate-drain charge	$Q_{gd}$		--	8	--	

**SOURCE TO DRAIN DIODE RATINGS CHARACTERISTICS**

Parameter	Symbol	Test conditions	Min.	Typ.	Max.	Unit
Continuous source current	$I_S$	Integral reverse p-n Junction diode in the MOSFET	--	--	10	A
Pulsed source current	$I_{SM}$		--	--	30	A
Diode forward voltage drop.	$V_{SD}$	$I_S=10A, V_{GS}=0V$	--	0.9	1.3	V
Reverse recovery time	$T_{rr}$	$I_S=10A, V_{GS}=0V, di/dt=100A/\mu s$	--	250	--	ns
Reverse recovery Charge	$Q_{rr}$		--	2.5	--	$\mu C$



Fig1. Output characteristics




Fig2. Maximum Drain Current vs. Case Temperature




Fig3. Gate charge characteristics




Fig 4. Capacitance Characteristics




Fig 5.  $R_{DS(ON)}$  vs junction temperature




Fig 6. Threshold Voltage vs Junction Temperature




Fig 7 . Safe operating area




Fig 8 . Transient thermal impedance




Fig 9. Forward characteristics of reverse diode




Fig 10 . Transfer characteristics




Fig 11. Gate charge test circuit & waveform





Fig 12. Switching time test circuit & waveform




Fig 13. Unclamped Inductive switching test circuit & waveform





Fig 14. Peak diode recovery dv/dt test circuit & waveform





## Disclaimer

- ◆ SINAI assumes no responsibility for equipment failures that result from using products at values that exceed, even momentarily, rated values (such as maximum ratings, operating condition ranges, or other parameters) listed in products specifications of any and all SINAI products described or contained herein.
- ◆ Specifications of any and all SINAI products described or contained herein stipulate the performance, characteristics, and functions of the described products in the independent state, and are not guarantees of the performance, characteristics, and functions of the described products as mounted in the customer's products or equipment. To verify symptoms and states that cannot be evaluated in an independent device, the customer should always evaluate and test devices mounted in the customer's products or equipment.
- ◆ In the event that any or all SINAI products(including technical data, services) described or contained herein are controlled under any of applicable local export control laws and regulations, such products must not be exported without obtaining the export license from the authorities concerned in accordance with the above law.
- ◆ This catalog provides information as of Nov. 2015. Specifications and information herein are subject to change without notice.